

DISC BRAKE FLUID DOT 4



Synthetic fluid for brake systems.

APPLICATIONS

- DISC BRAKE FLUID DOT 4 is recommended for brake and clutch systems of all vehicles using synthetic fluids when a DOT 4 level is required.
- DISC BRAKE FLUID DOT 4 is miscible with all other synthetic fluids of similar quality.
- DISC BRAKE FLUID DOT 4 is not miscible with mineral based fluids (LHM) and silicon based fluids.
- The color of the product can vary from colorless to amber.

PERFORMANCES

Specifications

Exceeds the level required by international specifications :

- SAE J 1704
- FMVSS 116 DOT 4
- ISO 4925

CUSTOMER BENEFITS

- Synthetic fluid.
- Very high dry and wet boiling points adjusted to ever increasing temperatures encountered in braking systems: prevents from "vapour lock".
- Resistant to moisture absorption.
- Viscosity suitable at cold as well as high temperatures.
- Provides corrosion protection for metals used in braking systems : cast iron, aluminium, steel, copper, brass etc.
- Compatible with rubber seals and hoses.

CHARACTERISTICS

DISC BRAKE FLUID DOT 4	Units	
Volumetric mass at 20°C	kg/dm ³	1.05 / 1.07
Viscosity at - 40°C (max) (Spec KV-40<1800mm ² /S)	mm ² /s	1200
Viscosity at 100°C (min)	mm ² /s	1,5
Dry boiling point ERBP (min)	°C	230
Wet boiling point WERBP (min)	°C	155

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS
16, rue de la République
F- 92800 PUTEAUX
1/1

DISC BRAKE FLUID DOT 4
July 2006
MGP/07/06



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.